

VELFAC 200 ENERGY

Opbygning med argon	Rudetype	R _w	R _w + C	R _w + C _{tr}	U _g DS/EN673	g _g DS/EN410	LT _g DS/EN410	R _a værdi
4-18-4-18-4*	Energy Std/Clear/Energy Std	33	-2	-6	0,53	0,53	0,74	96,0
4-18-4-16-6	Energy Std/Clear/Energy Std	37	-2	-6	0,55	0,53	0,73	96,0
6-16-4-14-8.4	Energy Std/Clear/Energy Std Lam Safe	41	-2	-6	0,61	0,53	0,73	95,0
8-14-4-14-8.8	Energy Std/Clear/Energy Std Lam Safe Sound	43	-2	-5	0,64	0,53	0,73	94,7
8.8-14-4-12-9.5	Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe	44	-2	-5	0,72	0,49	0,71	N/A
4-18-4-18-4* + 6	Energy Std/Clear/Energy Std + 6mm	46	-2	-6	0,47	0,49	0,67	N/A
8.8-12-6-12-8.8 + 10	Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe Sound + 10mm	53	-2	-4	0,61	0,45	0,63	N/A

Alle vinduesværdier gælder for et VELFAC vindue med 3-lags rude i målet:
B × H =1230 × 1480mm (det europæiske standardvindue).

* Denne rude er standardruden, hvor E_w = E_{ref} for vinduessystemet.